



公差/General Tolerance(mm)	
0	>3
~	>6
~	>10
~	>18
~	>30
~	>50
~	>80
~	>120
~	>180
~	>250
~	>315
~	>400
~	>500
±0.12	±0.18
±0.22	±0.28
±0.31	±0.37
±0.57	±0.80
±1.05	±1.15
±1.60	±2.20
±2.50	±7

ITEM	NAME OF PART	MATERIAL	NOTES
4	Nut	Copper alloy	/
3	Pin	Copper	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/Rated Voltage(V)/Current(A)	300/15	/	300/10
EC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级			
级/Pollution Degree	III/3	III/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	/	320/10	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	/	4	/
使用温度范围/Operating temperature(°C)	N=04~44P -40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL: SURFACE:

MAT NO.: /
STATUS: /
Appd: Lon CHH 2020.05.23
CHKD: /
DRAFT: BOYH 2018.09.30

DEGSON 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD
NAME: 2EDGVHM-5.08-XXP-1Y-00A(H)

DRAWING NO.: 2EDGVHM-5.08-C01
TYPE: CUSTOMER DRAWING
SCALE: 1:1
REV T1
SHEET 1/1

REV	ECN	DESCRIPTION	DRAFT	DATE
1				

